

AMENDMENTS TO THE CLAIMS:

This listing of claims will replace all prior versions, and listings, of claims in the application:

1. (Currently Amended) A method of allocating switch requests within a packet switch, the method comprising: ~~comprising the steps of~~
 - (a) generating switch request data for each input port indicative of the output ports to which data packets are to be transmitted;
 - (b) processing the switch request data for each input port to generate request data for each input port-output port pairing;
 - (c) generating an allocation plan for the switch for a frame of a defined number of packets, by a first stage in which allocation rules are applied such that the number of requests from each input port and to each output port is no greater than the defined frame length, and one or more further stages in which allocation rules are applied to allocate requests remaining unallocated by the previous stage.
2. (Currently Amended) A method according to claim 1, wherein unallocated switch requests are reserved ~~for use in a subsequent stage of switch request allocation~~ to a subsequent frame.
3. (Currently Amended) A method according to claim 1, wherein at least one of the stages is a process comprises: ~~comprises the steps of~~

- (a) generating switch request data for each input port indicative of the output ports to which data packets are to be transmitted;
- (b) processing the switch request data for each input port to generate request data for each input port-output port pairing;
- (c) generating an allocation plan by reducing the number of queue requests relating to each of one or both sets of ports by a value such that the number of requests relating to each member of the set or sets of ports is no greater than a predetermined frame value.

4. (Original) A method according to claim 3, wherein the transformation of the request data is done by using the summations of the requests from each input port.

5. (Previously Presented) A method according to claim 3, wherein the transformation of the request data is done by using the summations of the requests to each output port.

6. (Previously Presented) A method according to claim 3, wherein the reduction of the request data from each input port and to each output port is done, in such cases where the number of requests is greater than the maximum capacity of the corresponding input port or corresponding output port, the reduction being by a factor selected such that the number of requests from the corresponding input port and to the corresponding output port is no greater than the maximum capacity of the corresponding input port and the corresponding output port.

7. (Previously Presented) A method according to claim 3, wherein the reduction of the request data from each input port and to each output port is done using a common factor selected such that the number of requests from each input port and to each output port is no greater than the maximum request capacity of each input port and each output port.

8. (Currently Amended) A method according to claim 3, wherein the reduction of the request data comprises: ~~comprises~~

- (a) reducing the number of requests to each output port; and
- (b) reducing the number of requests in the resulting reduced request data that exceeds the capacity of each input port.

9. (Currently Amended) A method according to claim 3, wherein the transformation of the request data comprises: ~~comprises~~

- (a) reducing the number of requests from each input port; and
- (b) reducing the number of requests in the resulting reduced request data that exceeds the capacity of each output port.

10. (Previously Presented) A method according to claim 3, wherein the process is iterative, and is repeated one or more times in respect of input ports and output ports for which capacity remains available after the previous iteration is complete.

11. (Previously Presented) A method of packet switching wherein the input port-output port routing is allocated according to the method of claim 1 and the packets are switched on the basis of the allocated routing.

12. (Previously Presented) A packet switch in which the input port-output port routing is allocated in accordance with the method of claim 1.

13. (Original) A packet switch according to claim 12, wherein packets are switched from an input port to a specified output port in accordance with the allocated routing.